

SILICATE BLUSH REMOVER

DESCRIPTION AND USE

Removes the blush from puddled silicate sealers. Always read the product data sheet and do a test prior to starting the project. A mild, pleasant odor and non-corrosive components make it safe to both the user and the environment. Another real benefit of the product is that it does not foam on pickup, so that if you must vacuum the residue you will not waste time clearing foam or deforming. All of these characteristics make the soap easily treated in a waste reclaim system.

ADVANTAGES

Does not have non-ionics, sulfonates, high pH, harmful solvents, phosphates, or emulsifiers.

TECHNICAL DATA

Appearance & Odor: Pale amber color, mild citrus odor
Physical State: Liquid
pH: 10.5
Vapor Pressure (mmHg): As water
Vapor Density (air=1): As water
Boiling Point: 212° F
Freezing/Melting Point: 32° F
Specific Gravity (water =1): 1.13
Evaporation Rate: As water
Solubility in Water: Complete

PREPARATION

Protect adjacent and surrounding surfaces not intended to be treated. Cover foliage with polyethylene or other proven protective material.

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results. Best cleaning results are obtained when air and surface temperatures are 40° F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface.

PRE-TESTING

Always test prior to beginning full-scale cleaning operations. Testing should confirm cleaning effectiveness on each type of surface and stain designated to be removed. Testing also determines the desired dwell time and any potential for adverse reactions with adjacent materials. Allow test panels to dry thoroughly before evaluating final appearance and results.

DILUTION

Use undiluted (straight)

APPLICATION INSTRUCTIONS

Apply undiluted product to surface using a sprayer or squeegee. Let product dwell for 20 minutes. Do not allow product to dry on surface. Dwell time should be established during the testing phase. Then remove using a pressure washer. Blush should not be visible once area has been allowed to completely dry.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Do not get in eyes, on skin or clothing. If material comes in contact with clothing, wash before reuse. This product may dry out skin if used over prolonged periods of time. Keep container closed when not in use. Do not use for any other applications other than specified. Do not remove label. Read Safety Data Sheet for additional safety and health hazard information prior to use.

SPILL OR LEAK PROCEDURES

Check with the state, local, or federal regulations for waste disposal methods in the area. Wear gloves and goggles while doing cleanup. For large spills, dike and contain for intended use. For small spills, use a chemical absorbent product and place in approved container for disposal.

CONTAINER HANDLING/STORAGE

Store the product in a cool dry place. Keep container tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue and must be handled as if full.



SILICATE BLUSH REMOVER

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flush thoroughly with water for fifteen minutes. If irritation persists seek medical attention.

Skin: Wash off with soap and water.

If irritation develops, seek medical attention.

Inhalation: Remove to fresh air.

Ingestion: Do not induce vomiting. Drink large amount of water, seek medical attention if needed.

NOTICE

This product has been classified in accordance with the hazard criteria of the CFR.

DISCLAIMER

The information herein is given in good faith, but no warranty, either expressed or implied, is made. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot be sure or guarantee these are the only hazards, which exist.

CUSTOMER SERVICE

Factory personnel are available for assistance at 800-313-8505 and will send you additional information on products as necessary.

EaCo Chem. Inc.
765 Commerce Ave
New Castle PA 16101
Phone: (724) 656-1055
Fax: (724) 656-0757
www.eacochem.com

